

isc Silicon NPN Power Transistor


MJ15003

DESCRIPTION

- High DC Current Gain-
: $h_{FE} = 25(\text{Min})@I_C = 5A$
- Wide Area of Safe Operation
- Complement to the PNP MJ15004
- Minimum Lot-to-Lot variations for robust device performance and reliable operation


APPLICATIONS

- Designed for high power audio, disk head positioners and other linear applications.



ABSOLUTE MAXIMUM RATINGS($T_a=25^\circ\text{C}$)

SYMBOL	PARAMETER	VALUE	UNIT
V_{CBO}	Collector-Base Voltage	140	V
V_{CEO}	Collector-Emitter Voltage	140	V
V_{EBO}	Emitter-Base Voltage	5	V
I_C	Collector Current-Continuous	20	A
I_B	Base Current-Continuous	5	A
P_D	Total Power Dissipation@ $T_c=25^\circ\text{C}$	250	W
T_j	Junction Temperature	200	$^\circ\text{C}$
T_{stg}	Storage Temperature	-65~200	$^\circ\text{C}$



THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	0.7	$^\circ\text{C}/\text{W}$

isc Silicon NPN Power Transistor

MJ15003

ELECTRICAL CHARACTERISTICS

T_j=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	MAX	UNIT
V _{CEO(SUS)}	Collector-Emitter Sustaining Voltage	I _C = 50mA ; I _B = 0	140		V
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C = 5A; I _B = 0.5A		1	V
V _{BE(on)}	Base-Emitter On Voltage	I _C = 5A ; V _{CE} = 2V		2	V
I _{CEO}	Collector Cutoff Current	V _{CE} = 140V; I _B = 0		0.25	mA
I _{CBO}	Collector Cutoff Current	V _{CB} = 140V; I _E =0 V _{CB} = 140V; I _E =0; T _C = 150°C		0.1 2.0	mA
I _{EBO}	Emitter Cutoff Current	V _{EB} = 5V; I _C = 0		0.1	mA
h _{FE}	DC Current Gain	I _C = 5A ; V _{CE} = 2V	25	150	
I _{s/b}	Second Breakdown Collector Current with Base Forward Biased	V _{CE} = 100V, t= 1s, Nonrepetitive	1		A
C _{OB}	Output Capacitance	I _E = 0 ; V _{CB} = 10V; f _{test} = 1.0MHz		1000	pF
f _T	Current-Gain—Bandwidth Product	I _C = 0.5A ; V _{CE} = 10V; f _{test} = 0.5MHz	2		MHz

NOTICE:

ISC reserves the rights to make changes of the content herein the datasheet at any time without notification. The information contained herein is presented only as a guide for the applications of our products.

ISC products are intended for usage in general electronic equipment. The products are not designed for use in equipment which require specialized quality and/or reliability, or in equipment which could have applications in hazardous environments, aerospace industry, or medical field. Please contact us if you intend our products to be used in these special applications.

ISC makes no warranty or guarantee regarding the suitability of its products for any particular purpose, nor does ISC assume any liability arising from the application or use of any products, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages.