


查询54S00FM供应商

捷多邦, 专业PCB打样工厂, 24小时加

54/7400 ✓ 011065
 54H/74H00 ✓ 011069
 54S/74S00 ✓ 011574
 54LS/74LS00 ✓ 011068

QUAD 2-INPUT NAND GATE


CONNECTION DIAGRAMS
 PINOUT A



ORDERING CODE: See Section 9

PKGS	PIN OUT	COMMERCIAL GRADE	MILITARY GRADE	PKG TYPE
		$V_{CC} = +5.0 \text{ V} \pm 5\%$, $T_A = 0^\circ \text{ C to } +70^\circ \text{ C}$	$V_{CC} = +5.0 \text{ V} \pm 10\%$, $T_A = -55^\circ \text{ C to } +125^\circ \text{ C}$	
Plastic DIP (P)	A	7400PC, 74H00PC 74LS00PC, 74S00PC		9A
Ceramic DIP (D)	A	7400DC, 74H00DC 74LS00DC, 74S00DC	5400DM, 54H00DM 54LS00DM, 54S00DM	6A
Flatpak (F)	A	74LS00FC, 74S00FC	54LS00FM, 54S00FM	3I
	B	7400FC, 74H00FC	5400FM, 54H00FM	

PINOUT B



INPUT LOADING/FAN-OUT: See Section 3 for U.L. definitions

PINS	54/74 (U.L.) HIGH/LOW	54/74H (U.L.) HIGH/LOW	54/74S (U.L.) HIGH/LOW	54/74LS (U.L.) HIGH/LOW
Inputs	1.0/1.0	1.25/1.25	1.25/1.25	0.5/0.25
Outputs	20/10	12.5/12.5	25/12.5	10/5.0 (2.5)

DC AND AC CHARACTERISTICS: See Section 3*

SYMBOL	PARAMETER	54/74	54/74H	54/74S	54/74LS	UNITS	CONDITIONS
		Min Max	Min Max	Min Max	Min Max		
I_{CCH}	Power Supply Current	8.0	16.8	16	1.6	mA	$V_{IN} = \text{Gnd}$
I_{OCL}	Current	22	40	36	4.4		$V_{IN} = \text{Open}$
t_{PHL}	Propagation Delay	22 15	10 10	2.0 2.0	4.5 5.0	ns	Figs. 3-1, 3-4

*DC limits apply over operating temperature range; AC limits apply at $T_A = +25^\circ \text{ C}$ and $V_{CC} = +5.0 \text{ V}$.